

AND THE PAVEMENT MARKING PLAN THIS SHEET.

NOT TO BE PAVED.

6. SEED, FERTILIZE AND MULCH ALL DISTURBED AREAS THAT HAVE BEEN DENUDED AND ARE

SEDIMENT CONTROL MEASURES, REMOVE DEBRIS, AND DISPOSE OF OFF-SITE.

7. AFTER GRASS AREAS HAVE BEEN ESTABLISHED AND ACCEPTED, CLEAN UP ALL EROSION AND

DEVICËS (DRUMS). *

REQUIREMENTS.

* THESE DEVICES SHOULD BE REMOVED WHEN NO LONGER REQUIRED IF THE

THERE WILL BE TIMES WHEN THESE REQUIREMENTS WILL NOT WORK DUE TO

THE RESIDENT ENGINEER TO RECEIVE AN EXCEPTION TO THE

INSTALLATION AND REMOVAL OF THESE DEVICES PRESENT LITTLE DIFFICULTY.

UNUSUAL CIRCUMSTANCES. THESE CIRCUMSTANCES SHALL BE DISCUSSED WITH

HIGH INTENSITY AMBER STROBE LIGHTS SHALL CONSIST OF A DOUBLE FLASH UNIT

FLASHES PER MINUTE. STROBE LIGHTS SHALL BE APPROXIMATELY 6-5/8 INCHES

OPERATIONS CONDUCTED AT NIGHT OFTEN REQUIRE ADDITIONAL LIGHTING

ENCLOSED WITHIN AN AMBER COLORED LENS. FLASH RATE SHALL BE 80 ±10

TO SUFFICIENTLY ILLUMINATE THE WORK AREA IN THE TEMPORARY

TRAFFIC CONTROL ZONE. LIGHTING SHALL BE ARRANGED SO AS NOT T

AND EXITING THE WORK AREA SHOULD BE EQUIPPED WITH AND HAVE

A TRUCK WITH AT LEAST ONE ROTATING AMBER LIGHT OR HIGH INTENSITY AMBER

STROBE LIGHT SHALL BE PARKED 50' TO 100' IN ADVANCE OF THE FIRST WORK

CREW. THE ROTATING AMBER LIGHT CAN BE EITHER TRUCK OR TRAILER MOUNTED

BUT MUST BE RELOCATED OUT OF THE ROAD (PREFERABLY WITHIN THE PROPOSED

SUBDIVISION PROJECT) AT THE END OF EACH WORK PERIOD. RELOCATION TO THE

POSITION) ON ALL ADVANCE WARNING VEHICLES LOCATED WITHIN THE RIGHT OF

TURNED FOR "AFTER-IMPACT PROJECTORY" INTO A SAFE AREA. THE TMA VEHICLE

SHALL NOT BE USED AS WORK VEHICLE. ANY MATERIAL AND/OR EQUIPMENT ON THE TMA VEHICLE SHALL BE PROPERLY SECURED TO PREVENT SPILLAGE IF STRUCK BY A VEHICLE.

WAY. THÉ VEHICLE PARKING BRAKE SHALL BE SET WITH THE FRONT WHEELS

4. TRUCK MOUNTED ATTENUATORS SHALL BE INSTALLED (IN FULL LOCK DOWN

INTERFERE WITH OR IMPEDE TRAFFIC APPROACHING THE WORK AREA IN

EITHER DIRECTION. DURING NIGHT OPERATIONS, ALL VEHICLES ENTERING

OPERATING AT LEAST ONE ROTATING AMBER LIGHT OR HIGH INTENSITY

IN DIAMETER AND 7-1/2 INCHES IN HEIGHT OR GREATER.

2. NIGHT WORK LIGHTING:

AMBER STROBE LIGHT.

SHOULDER IS PROHIBITED.

22247

3. PAVEMENT MARKING STRIPES AND ARROWS ARE TO BE

WHITE UNLESS OTHERWISE INDICATED.